

CONNECTED PRO SERIES

3120HL

Smart Garage Door Opener Belt or Chain Drive











Smart Garage Capabilities

» Security – Instantly know if someone is operating your garage door without permission.

- » Convenience Open your door for family members, deliveries or service providers from anywhere with your smart device.
- » Safety Have garage door automatically close at a specific time or after an elapsed time period in case it's left open.

Durable, Reliable Performance

The strong 24 Volt DC motor operates most properly balanced residential sectional doors up to 10' high. Model G3120HL has an opening speed of 7.0" per second*.

Soft Start and Stop Control

DC technology allows your door to begin and end its movement smoothly instead of abruptly whenever you operate it, creating less noise and less wear on the door.

GenieSense™ Monitoring

Automatic force profiling and diagnostic technology improves safety by stopping operation when significant changes occur.

Dependability

The quality built into a Model G3120HL is backed by Limited Lifetime motor and Limited 15-Year belt drive rail Warranties⁶ (5-Year chain drive rail).

Integrated LED Lighting

Integrated LED lighting system provides bright, long-lasting, energy-efficient illumination designed to eliminate garage door opener remote interference.

Battery Backup Capable (Model G3120HL-B) Don't get locked outside the garage when the power goes out! The optional battery unit can easily be added to your opener.


^{*+/- 0.5&}quot; per second for sectional doors

[♦] Limited non-transferable warranty. See Programming, Operation and Maintenance manual for details.



Aladdin Connect® **Integrated Wi-Fi connectivity**

Remotely monitor and control your garage door from almost anywhere with your smart device. Time-based features allow you to set door to automatically close and/or notify



Scan code for complete list of Smart Home Partners











OPTIONS



Wireless Keypad: Easy-to-program, back-lit keypad, control up to 6 openers, Auto-Seek Dual Frequency (315/390 MHz), available in off-white.



Integrated Battery Backup Model (G3120HL-B):

Allows operation in the event of power outage.



1-Button Remote: Simple design, Auto-Seek Dual Frequency, compatible with all Intellicode® equipped Genie openers.



Wireless Wall Console: Wireless, up to 30 second delay, work light button, compatible with most Genie Intellicode® openers made since 2013.



Heavy-Duty Rail: Smooth operation, prevents rail deflection, door travel aesthetics.

CONNECTED PRO SERIES

G3120HL

Smart Garage Door Opener Belt or Chain Drive

STANDARD EQUIPMENT AND LIMITED WARRANTIES







Safety Beams, Motion Wall Console, 3-Button Remote

Lifetime: Motor

15 Years: Rail (Belt Drive)

5 Years: Rail (Chain Drive)

5 Years: **Parts**

1 Year: Accessories

FFATURES

Power and Control

DC Motor Smart Technology: The DC motor provides quiet operation with Soft Start and Stop control. Smooth operation reduces noise and wear on the garage door.

C-Channel Rail: Strong rail design promotes durability and safety with cleaner appearance.

Belt or Chain Drive: Select belt drive option for quieter operation or chain drive for economical value.

Safety and Security

Safe-T-Beam® Non-Contact Reversing System: When objects pass through the infrared beam, the garage door automatically stops closing and reverses to open without having to make physical contact with the door.

Intellicode® Access Security System: Prevents unauthorized remotes from controlling your door by changing code each time the opener is operated.

Sure-Lock™ Control: Lock out remote controls and wireless keypad at any time.

Convenience

Integrated LED Lighting:

High-efficiency, integrated LED lighting is frequency tuned not to interfere with transmitter range and provides bright, aesthetically pleasing light. Integrated lighting is designed for thousands of hours of maintenance-free use.

Patented Frequency Switching:

The opener automatically uses either 315 or 390 MHz frequency to avoid potential nearby interference, such as military base equipment, to help ensure the opener operates properly.

Pre-Programmed Remote: Ready to use out-of-the-box with simple steps to change the programming if needed.

HomeLink® and Car2U® Compatible: Works with current and ALL previous versions of HomeLink® or Car2U®. No additional external repeater kit or compatibility bridge needed.

6' Power Cord: For high ceiling applications.

CALIFORNIA RESIDENTS - This opener has the option to add battery backup. As required by SB-969, all newly installed openers must have battery backup as of 7/1/19. To order this opener with battery backup, refer to Models G3120HL-B. If needed, visit www.geniecompany.com or ask your Genie dealer for details.

♦ Limited non-transferable warranty. See Programming, Operation and Maintenance manual for details.

© 2025 The Genie Company. Genie, IntelliG, ReliaG, Safe-T-Beam, Intellicode, Aladdin Connect and the Genie logo are registered trademarks and Sure-Lock are trademarks of GMI Holdings, Inc., d/b/a The Genie Company. Consistent with our policy of continuing product improvement, we reserve the right to change product specifications without notice or obligation. HomeLink is a registered trademark of Gentex Corporation. Car2U is a registered trademark of Lear Corporation. |© 2025 Google LLC All rights reserved. Google Assistant and Google Play are trademarks of Google LLC. | Amazon, Echo, Alexa, and all related logos are trademarks of Amazon.com Inc. or its affiliate









