

WALL MOUNT PRO SERIES 70H

Smart Garage Door Opener Wall Mount







Durable Motor with Soft Start and Stop Control



PRODUCT HIGHLIGHTS

Wall Mount Design

Compact design fits into tight side room spaces between track and wall. No rail required. Ideal for garages with beam obstructions which prevent installation of a traditional opener.

Smart Garage Capabilities

- » Security Instantly know if someone is operating your garage door without permission.
- » Convenience Open your door for family members, deliveries or service providers from anywhere with your smart device.
- » Safety Have garage door automatically close at a specific time or after an elapsed time period in case it's left open.

Quiet, Powerful Performance

24 Volt DC motor provides maximum power to operate doors up to 850 lbs at a speed of 7.5" per second*.

Dependability

The quality built into a Model 6170H is backed by Limited Lifetime motor Warranty⁽⁾.

Soft Start and Stop Control

DC technology allows your door to begin and end its movement smoothly instead of abruptly whenever you operate it, creating less noise and less wear on the door.

GenieSense™ Monitoring

Automatic force profiling and diagnostic technology improves safety by stopping operation when significant changes occur.

Smart LED Lighting

Bright LED light fixture with the flexibility to place wherever desired in the garage.

Battery Backup Capable (Model 6170H-B)

Don't get locked outside the garage when the power goes out! The optional battery unit can easily be added to your opener.



^{*+/- 0.5&}quot; per second for sectional doors.

[♦] Limited non-transferable warranty. See Programming, Operation and Maintenance manual for details.





Shown with optional battery backup (6170H-B)

Aladdin Connect® **Integrated Wi-Fi connectivity**

Remotely monitor and control your garage

door from almost anywhere with your smart device. Time-based features allow you to set door to automatically close and/or notify after a set length of time; as well as schedule a specific hour and minute to close the door and/or notify when it does. Allows for multiple individual user accounts so you can provide virtual key access for your garage door to a friend, relative, or service person for a certain time, a range of time, or permanently.

Scan code for complete list of Smart Home Partners











Non-Wi-Fi Model 6070H: The Model 6070H is also available, offering the same reliable performance and features without built-in Wi-Fi.

OPTIONS



Wireless Keypad: Easy-to-program, back-lit keypad, control up to 6 openers, Auto-Seek Dual Frequency (315/390 MHz), available in off-white.



Integrated Battery Backup Model (6170H-B):

Allows operation in the event of power outage.



1-Button Remote: Simple design, Auto-Seek Dual Frequency, compatible with all Intellicode® equipped Genie openers.

WALL MOUNT PRO SERIES

6170H

Smart Garage Door Opener Wall Mount

STANDARD EQUIPMENT AND LIMITED WARRANTIES









LED Light Fixture, Safety Beams, Wireless Wall Console, 3-Button Remote

Lifetime: Motor

5 Years: **Parts**

1 Year: Accessories

FFATURES

Power and Control

DC Motor Smart Technology: The DC motor provides guiet operation with Soft Start and Stop control. Smooth operation reduces noise and wear on the garage door.

Wall Mount Design: No rail required. Beneficial for installing in garages with beam obstructions. Powerful yet compact size allows for more placement options, especially in tight spaces next to the garage door.

Safety and Security

Safe-T-Beam® Non-Contact **Reversing System:** When objects pass through the infrared beam, the garage door automatically stops closing and reverses to open without having to make physical contact with the door.

Intellicode® Access Security System: Prevents unauthorized remotes from controlling your door by changing code each time the opener is operated.

Convenience

LED Light Fixture: Light fixture provides bright, LED lighting with the flexibility to place fixture wherever desired in the garage.

Patented Frequency Switching:

The opener automatically uses either 315 or 390 MHz frequency to avoid potential nearby interference, such as military base equipment, to help ensure the opener operates properly.

Pre-Programmed Remote: Ready to use out-of-the-box with simple steps to change the programming if needed.

HomeLink® and Car2U® Compatible: Works with current and ALL previous versions of HomeLink® or Car2U®. No additional external repeater kit or compatibility bridge needed.

6' Power Cord: For high ceiling applications.

CALIFORNIA RESIDENTS – This opener has the option to add battery backup. As required by SB-969, all newly installed openers must have battery backup as of 7/1/19. To order this opener with battery backup, refer to Models 6170H-B. If needed, visit www.geniecompany.com or ask your Genie dealer for details.

 ${\tt \lozenge \ Limited \ non-transferable \ warranty}. \ See \ Programming, \ Operation \ and \ Maintenance \ manual \ for \ details.}$

© 2025 The Genie Company. Genie, IntelliG, ReliaG, Safe-T-Beam, Intellicode, Aladdin Connect and the Genie logo are registered trademarks and Sure-Lock are trademarks of GMI Holdings, Inc., d/b/a The Genie Company. Consistent with our policy of continuing product improvement, we reserve the right to change product specifications without notice or obligation. HomeLink is a registered trademark of Gentex Corporation. Car2U is a registered trademark of Lear Corporation. |© 2025 Google LLC All rights reserved. Google Assistant and Google Play are trademarks of Google LLC. I Amazon, Echo, Alexa, and all related logos are trademarks of Amazon, com Inc. or its affiliate









